



REVENUE **GENERATING** MODEL

LOWER FLOORS OF THE PROTO-TYPE IS
RESERVED FOR THE
OWNERS AND THE
REMAINING 2 FLOORS
(2 BHK & STUDIO APARTMENT) ARE FOR RENTALS

RESIDENCE BLOCK BALCONIES, TERRACES/GARDENS

POSSIBLE NODE FOR INTERACTION





SECOND FLOOR PLAN

SPACES OF SOCIAL INTERACTIONS


THE OWNERS OF THE PLOTS UNDER THE LANDPOOLING SCHEME ARE PRIMARILY THE RESIDENTS OF THE NEIGHBOURING VILLAGES.

THE SPACES & NEIGHBOURHOODS THEY AREACCUSTOMED TO ARE PRIMARILY SOCIALLY INTERACTIVE SPACES. EXCHANGING WORDS/GOODS OVER BOUNDARY WALLS, WOMEN DRYING SEEDS, MANGO JELLY, PAPADS ETC ON TERRACES IN SUMMERS, KIDS PLAYING GAMES/FLYING KITES & SLEEPING ON TERRACES ARE SOME EXAMPLES


THROUGH THIS DESIGN CHALLENGE WE INTEND TO KEEP ALIVE THE SOCIAL INTERACTION FOUND IN THE VILLAGES BY DESIGNING CONTEMPORARY HOUSES WITH A TOUCH OF TRADITIONALITY.

SOCIAL INTERACTIONS AT DIFFERENT LEVELS NOT ONLY STRENGTHENS THE BOND BETWEEN THE RESIDENTS BUT ALSO AIDS NATURAL SURVEILLANCE.

THE STAGGERED INTERACTION PATTERNS ENSURES PRIVACY OF THE INDIVIDUALS.



FIRST FLOOR PLAN



STAGGERED VIEWS OF



SPACES OF SOCIAL INTERACTIONS

sheet no.1

6

SECOND FLOOR PLAN

FIRST FLOOR PLAN

ENTRY

LOCALLY AVAILABLE OXYGEN **GIVING PLANTS**



5 Peace lily

Syngonium







OUTDOOR SEATING (ARUGU) TO AID SOCIAL INTERACTION
















GROUND FLOOR PLAN







RAT-TRAP BOND WITH COCONUT HUSK FILLER AS INSULATION

Fly-ash bricks in Rat-trap bond - Low cost and



TERRACE GARDEN
Cool roof strategies to cut down the maximum heat entering from the roof



FILLER SLAE

WALEK MANAGEMENI
Step 1: Total water requirement for a residence of 10 occupants (Source: NBC)

- Drinking water = 5 L X 10 people = 50 LPD

- Domestic water = 70 L X 10 people = 700 LPD

- Flushing water = 40 L X 10 people = 400 LPD

- Hot water = 20 L X 10 people = 200 LPD

- Irrigation water = 0.5 x 500 SF = 250 LPD
 Total = 1600 LPD

Step 2: Amount of Rainwater that can be collected in a year

• Annual rainfall of Amaravati = 1067 mm

• Runoff areas (Area x coefficient x Annual rainfall) :

• Roof = 100 x 0.85 x 1067 = 90.6 KL / year

• Pavers = 35 x 0.6 x 1067 = 22.4 KL / year

- Landscaping = 50 x 0.35 x 1067 = 18.6 KL / year

- Total = 13.17 KL / year

- Average per day = 131.7/365 = 0.36 KL = 3600 L

Step 3: Size of Rain Water Harvesting pit required
For Amaravati peak rainfall occurs in July i.e) 250 mm
On one day it can be 250/15 days = 16.6 mm/day

- On one day it can be 250/15 days = 16.6 mm /d
 Maximum Flow on peak dayy
 Roof = 100 x 0.85 x 16.6 = 1.4 KL/day
 Pavers = 35 x 0.6 x 16.6 = 0.35 KL /day
 Landscaping = 50 x 0.35 x 16.6 = 0.3 KL/day
 Total = 2.05 KL/ day
 Percolation through one pit
 Percolation rate = 0.02 m/hr for 1 sqm space
 Assume pit size = 2 x 2 = 4 sqm
 Percolation from 1 pit = 4 x 0.02 = 0.08 KL/hr
 Percolation in a day = 0.08 x 24 = 1.92 KL/day
 No. of pits required = 2.05/1.92 = 1


CHINA MOSAIC TILES

LIFT

SOUTH FACING PLOT UNIVERSAL ACCESSIBILITY Incremental lift provision

COOL ROOF STRATEGIES TO

CUT DOWN THE MAXIMUM HEAT INTO THE BUILDING



WATER PROOFING FOR TERRACE GARDEN

ELECTRICITY MANAGEMENT PAYBACK PERIOD: 5 YEARS

- PATBACK PERIUD: 3 YEARS
 Step 1: Solar PV Power generation
 Space requirement for 1 kW = 12 Sqm (Refered from solar PV catalogues)
 Total Space available = 60 Sq.m
 Possible installed Solar PV. size = 60 sqm/12 = 5 KW
 Possible Annual power generation = 5 kW Y 4, 5 Y
- Possible Annual power generation = 5 kW X 4.5 X 300 Days = 6750 kWh

- Step 2: Payback period for solar PV panels
 Annual Savings = 6750 kWh
 Let's assume electricity rate is Rs. 7 / kWh
 Savings = 6750 kWh X Rs. 7 = Rs. 47.250/• Solar PV Installation cost: I kW costs Rs.
 80.000/-Total Installation cost = 5 kW X Rs. 80,000 =
- 4,00,000/-4,00,000/• Pay back = Initial Cost / Annual Savings = 4,00,000/80,000 = 5 Years

HOT WATER MANAGEMENT PAYBACK PERIOD: 3.5 YEARS

Step 1: Total Hot water demand of the residence
• Total Population: Owners(5) + Tenants-2BHK (4) +
Tenants-Studio Apartment(1) = 10 Occupants Hot water demand per person = 20 LPD (Source:

Hot water demand per person = 20 LPD (Source: NBC)
Total hot water demand = 10 x 20 = 200 LPD
Step 2: Installation of solar thermal panels
Area required for installation = Generally 0.03Sqm required for IL
Total Space required for installation on roof top = 200 X 0.03 sqm = 6 sqm
Step 3: Cost of Installation of solar thermal panels
Cost for installation = Generally Rs 250/11

Cost for installation = Generally Rs. 250/1L Cost for installation in the residence = 200 L X Rs.

- Cost for installation in the residence = 200 L X Rs.
 250 = Rs 50,000/Step 4: Cost if conventional electric system is used
 If we use electric geyser 25L home geyser
 requires 2.5 kW electricity
 It takes 0.5 hrs to heat 25 L

- So, power consumption is 2.5 kW X 0.5 Hrs = 1.25 kWh for 25 Li.e. 0.05 kWh/L for a day

 Annual requirement = 0.05 kWh X 200 Days = 10 kWh/Your
- kWh/Year kWh/Year
 Total power requirement = 200 L X 10 kWh = 2000 kWh
 If electricity rate is Rs. 7/kWh
 Money spent is 2000 kWh X Rs. 7 = Rs. 14,000/Step 5: Calculation of payback period
 Initial Cost: Rs. 50,000/Apple 15 carges Ps. 14,000 /

- Annual Savings: Rs. 14,000/ Pay back: 50,000/14,000 = 3.57 Years

SPACES OF SOCIAL INTERACTIONS







EAST ELEVATION



WEST ELEVATION





SOLAR PV & SOLAR THERMAL PANELS **SET BACK**